

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/085777 A1

(51) International Patent Classification⁷: **E05C 19/02**,
E05F 3/14, 5/10, F16F 9/12

(21) International Application Number:
PCT/IT2003/000535

(22) International Filing Date:
8 September 2003 (08.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
TO2003U000058 27 March 2003 (27.03.2003) IT

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and
(72) Inventor: **CULTRARO, Antonino** [IT/TT]; Via Montegrappa, 26, I-10098 Rivoli (Torino) (IT).

(74) Agents: **QUINTERNO, Giuseppe** et al.; Jacobacci & Partners SpA, Corso Regio Parco, 27, I-10152 Torino (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A DEVICE FOR SLOWING THE MOVEMENT OF A DOOR, DRAWER OR SIMILAR MOVABLE MEMBER, HAVING RELEASABLE LOCKING MEANS



(57) Abstract: A device (15) for slowing the movement of a door (2) urged by unidirectional thrust means (4), including a casing (17) fixable to a structure (S) and defining a chamber (18) filled with a viscous fluid, and a rotor (31). The rotor (31) includes a disc portion (32) and a shaft portion (33) protruding through the lid (21) of the casing (17) in such a way as it can be associated with the door (2). The base surface (23a) of the chamber (18) has a recess (51) operable to house a pivotable arm (52). The arm (52) has a pin portion (54) protruding into the chamber (18). The lower surface (62) of the disc portion (32) of the rotor (31) has a groove (70) for engaging the pin portion (54) of the arm (52). At one end (73), the groove (70) has a cam (76) dividing it into a return path (75) and a forward path (74) for the pin portion (54) so as to define a locking position for the rotor (31) in cooperation with the thrust means (4).